

PERSONNEL AIRLOCK SMART-LINE



Construction:

Folding airlock with self-closing doors; large flaps, which are also viewing windows. Self-closing door elements made of composite panels. The flaps ensure a directed air flow towards the work area.

The roof and floor elements of the shower are made of 2 mm aluminium. The door element is made of a 3 mm thick aluminium composite material, the side walls of the shower are made of hard-foamed, antistatic, washable, 8 mm thick sandwich panels, PVC-coated on both sides.

Individual chamber		foldable	
Shower chamber		plug-in	
Compatibility		SMART-LINE	
Model 750	Dimensions [mm]	750 x 750 x 2.000	
	Weight, indivi- dual chamber [kg]	26	
	Weight, 3 cham- bers [kg]	83	
	Dimensions [mm]	1.000 x 1.000 x 2.000	
Model 1000	Weight, indivi- dual chamber [kg]	30	
Мос	Weight, 3 cham- bers [kg]	102	

Water connection

Geka

Optional equipment

Automatic shower in line with TRGS 519 regulations 4- and 5-chamber variants also available



MODELS / ACCESSORIES / OPTIONS

Model 750		Model '	Model 1000		Accessories / Options	
735	2-chamber (Clean area and shower)	733	2-chamber (Clean area and shower)		BO15219 Adapter base in tarpaulin	
736	2-chamber (Shower and conta- minated area)	734	2-chamber (Shower and conta- minated area)		BO16202 Sink in shower chamber	
713	3-chamber airlock	719	3-chamber airlock	F	BO16505 Transport rack	
714	3-chamber airlock (2 x shower)	720	3-chamber airlock (2 x shower)	F	BO16665 Utility connection	
737	4-chamber airlock	723	4-chamber airlock		BO16113 Bench with lockers and heating	
715	4-chamber airlock (Clean, shower, shower, contamina- ted)	721	5-chamber airlock		AU3898 Repair tarpaulin fabric	
716	5-chamber airlock	707	Individual chamber		BO23055 Automatic shower in line with TRGS 519	
717	Individual chamber	722	Individual chamber shower	_	regulations	
718	Individual chamber	_				

shower

(in) (f) (ii) (iii)