

WASTEWATER MANAGEMENT

Water filtration unit AS 200 | Article-Nr. 823



Power [kW]	0,45
Max. flow rate [l/min]	28
Max. medium temperature [°C]	90
Power connection [V]	230
Filter stages	2
Filter type [μ]	1, 220
Protection class	IP 44
Dimensions [mm]	611 x 240 x 517
Weight [kg]	16

Water filtration unit AS 300 | Article-Nr. 328



Power [kW]	0,45
Max. flow rate [l/min]	30
Max. medium temperature [°C]	90
Power connection [V]	230
Filter stages	3
Filter type [μ]	1, 50, 220
Protection class	IP44
Dimensions [mm]	775 x 285 x 695
Weight [kg]	25

Water filtration unit AS 300 CG | Article-Nr. 539



Power [kW]	0,45
Max. flow rate [l/min]	30
Max. medium temperature [°C]	90
Power connection [V]	230
Filter stages	4
Filter type [μ]	1, 50, 2x 220
Protection class	IP 44
Dimensions [mm]	653 x 464 x 773
Weight [kg]	56
Integrated coarse filter	

ACCESSORIES / OPTIONS

Wastewater filter 10"



AU415
1 µ

AU541
5 µ

AU543
25 µ

AU1153
200 µ

Options



462
Coarse pre-filter



BO7511
Rack for coarse
filter



BU1504a
Fresh water hose



BU1504
Wastewater hose



BU1629
Wastewater hose
with proximity
switch (for AS 300
and AS 300 CG)